

# INDUSTRIAL WATER CHILLER

## TAEvo-015 / 020



### Product Specifications

CAPACITIES		015	020
Cooling Capacity	ton	1.55	2.04
<i>Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature</i>			
BTU/hr		18,575	24,463
Tank Volume	gal	15.4	15.4

DIMENSIONS		015	020
Width	in	22.1	22.1
Depth	in	49.2	49.2
Height	in	29.5	29.5
Weight	lbs	280	291

### Features / Benefits

- UL & CE listed
- Stocked for quick delivery
- Indoor / Outdoor model
- Closed loop water circulation
- Optimal temperature control
- Condenser coil filters
- Closed expansion kit
- Crankcase heaters

ELECTRICAL		015	020
Volts		460	460
Phase		3	3
Hertz		60	60
FLAmps		8.4	9.9

### Options

- Remote start/stop kit
- Open expansion kit
- Glycol filling kit
- Non ferrous water circuit
- Condenser coil coating
- Low ambient package for colder climates

MISC SPECS		015	020
Refrigerant		R407C	R407C
Protection Class		IP 54	IP 54
Flow Rate	gpm	5.53	6.79
Pump Power	kW	0.75	0.75
Fan Power (each)	kW	0.185	0.185
# of Fans		1	1
Noise Level	dBa	47.2	43.4
Connection Size	npt	3/4"	3/4"