

INDUSTRIAL WATER CHILLER

TAEvo-M05 / M10



Features / Benefits

- CE Approved
- Stocked for quick delivery
- Closed loop water circulation
- Optimal temperature control
- Condenser coil filters
- Crankcase heaters

Options

- Remote start/stop kit
- Open expansion kit
- Glycol filling kit
- Non ferrous water circuit
- Condenser coil coating
- Low ambient package for colder climates

Product Specifications

CAPACITIES		M05	M10
Cooling Capacity	ton	0.51	0.99
<i>Capacity based on 45°F water outlet temp.; 10°F delta t @ 95°F ambient temperature</i>			
BTU/hr		6,012	11,904
Tank Volume	gal	7	7

DIMENSIONS		M05	M10
Width	86 in	22.6	22.6
Depth	in	26.3	26.3
Height	in	30.9	30.9
Weight	lbs	170	184

ELECTRICAL		M05	M10
Volts		230	230
Phase		1	1
Hertz		60	60
FLAmps		8.2	14

MISC SPECS		M05	M10
Refrigerant		R22	R22
Protection Class		IP 32	IP 32
Flow Rate	gpm	-	-
Pump Power	kW	0.33	0.33
Fan Power (each)	kW	0.186	0.186
# of Fans		1	1
Noise Level	dBa	-	-
Connection Size	npt	1/2"	1/2"