

REFRIGERANT R407C

Page: 1 Compilation date: 5/19/2015 Revision date: 3/6/2018 Revision No: 1a

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: REFRIGERANT R407C

Product code: R407C

Synonyms: GENETRON 407C

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Refrigerant PC16: Heat transfer fluids.

1.3. Details of the supplier of the safety data sheet

Company name: Industrial Water Chiller

(A Division of T. J. Snow)

120 Nowlin Lane

Chattanooga

Tennessee

37421

USA

Tel: 1-800-934-0785

Email: customerservice@tjsnow.com

1.4. Emergency telephone number

Emergency tel: 1-800-934-0785

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Press. Gas: H280

Most important adverse effects: Contains gas under pressure; may explode if heated.

2.2. Label elements

Label elements:

Hazard statements: H280: Contains gas under pressure; may explode if heated.

Hazard pictograms: GHS04: Gas cylinder



Signal words: Warning

Precautionary statements: P260: Do not breathe gas/vapours/spray.

REFRIGERANT R407C

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P284: [In case of inadequate ventilation] wear respiratory protection.

P308+313: IF exposed or concerned: Get medical attention.

P410+403: Protect from sunlight. Store in a well-ventilated place.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

REFRIGERANT R134A - REACH registered number(s): 01-2119459374-33

EINECS	CAS	PBT / WEL	CLP Classification	Percent
212-377-0	811-97-2	Substance with a Community workplace exposure limit.	Press. Gas: H280	50-70%
PENTAFLUOF	ROETHANE - R	EACH registered number(s): 01-2119	9485636-25	
206-557-8	354-33-6	Substance with a Community workplace exposure limit.	Press. Gas: H280	10-30%
DIFLUOROME	THANE			
200-839-4	75-10-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the
	affected skin with running water for 10 minutes or longer if substance is still on skin. Do not
	use hot water. If frostbite has occurred call a physician.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Injestion is unlikely because of the physical properties and is not expected to be hazardous.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact. Frost-bite may occur causing the affected area to become white and numb.

Eye contact: There may be irritation and redness. Corneal burns may occur. May cause permanent damage.

Ingestion: Not applicable.

Inhalation: Inhalation may produce the following symptoms: Shortness of breath, dizziness, weakness, nausea, headache, narcosis, irregular cardiac activity. May cause cardiac arrhythmia.

REFRIGERANT R407C

Page: 3

Delayed / immediate effects: May cause cardiac arrhythmia.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Do Not give adrinaline or similar drugs.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: The product is not flammable. Suitable extinguishing media for the surrounding fire should be used. Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Stop release if safe to do so. Prevent from entering sewers, basements and work pits, or any place where the accumulation can be dangerous.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Material evaporates. Ventilate the area, especially low or enclosed places where heavy vapours might collect.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Store at a temperature not exceeding 45°C.

Suitable packaging: Must only be kept in original packaging.

REFRIGERANT R407C

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

REFRIGERANT R134A

Workplace ex	posure limits:	F	Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	4240 mg/m3	-	-	-
PENTAFLUOF	ROETHANE			
EU	1000 ppm	-	-	-
DIFLUOROME	THANE			
UK	1000 ppm	-	-	-
NEL/PNEC Val	lues			

Hazardous ingredients:

REFRIGERANT R134A

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	2476 mg/m3	Workers	Systemic
DNEL	Inhalation	2476 mg/m3	Consumers	Systemic
PNEC	Fresh water	0.01 mg/l	-	-
PNEC	Marine water	0.75 mg/l	-	-
PNEC	Microorganisms in sewage treatment	73 mg/l	-	-
DNEL	Inhalation	13936 mg/m3	Workers	Systemic
PNEC	Fresh water sediments	0.75 mg/kg	-	-

PENTAFLUOROETHANE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	16444 mg/m3	Workers	Systemic
DNEL	Inhalation	1753 mg/m3	Consumers	Systemic
PNEC	Fresh water	0.1 mg/l	-	-
PNEC	Fresh water sediments	0.6 mg/kg	-	-

DIFLUOROMETHANE

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation (developmental tox)	13936 mg/m3	Workers	Systemic

REFRIGERANT R407C

Page: 5

DNEL	Inhalatio	n (developmental tox)	2476 mg/m3	Consumers	Systemic	
PNEC		Fresh water	0.142 mg/l	-	-	
PNEC	F	resh water sediments	0.534 mg/kg	-	_	
8.2. Exposure c	ontrols					
•				. Ensure there is exhaust v	entilation of the	
Respirator	ry protection:	-	apparatus must be av	ailable in case of emergen educing the oxygen availat		
Han	d protection:	Protective gloves.				
Eye protection: Safe		Safety glasses. Ensure eye bath is to hand.				
Ski	in protection:	Protective clothing.				
ection 9: Physi	cal and cher	nical properties				
9.1. Information	n on basic phy	sical and chemical prop	perties			
	State:	Liquified gas				
	Colour:	Colourless				
	Odour:	Barely perceptible odour				
Evaporation rate: No data available.		No data available.				
	Oxidising:	Not applicable.				

Oxidising:	Not applicable.		
Solubility in water:	No data available.		
Also soluble in:	Most organic solvents.		
Boiling point/range°C:	-43.9	Melting point/range°C:	No data available.
Flammability limits %: lower:	Not applicable.	upper:	Not applicable.
Flash point°C:	Not applicable.	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	Not applicable.	Vapour pressure:	10.999 Bar at 20oC
pH:	No data available.		

9.2. Other information

Other information: Liquid density: 1159 kg/m3 at 20oC Vapour density: 4.629 kg/m3 at boiling point. Molecular weight: 86.20 g/mol.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

REFRIGERANT R407C

10.4. Conditions to avoid					
Conditions to avoid:	Heat. Hot surfaces. S	Sources of ignition. Flames.			
10.5. Incompatible materials					
Materials to avoid:	Strong oxidising ager	nts. Strong acids.			
10.6. Hazardous decompositi	ion products				
Haz. decomp. products:	In combustion emits	toxic fumes.			
Section 11: Toxicological inf	ormation				
11.1. Information on toxicolo	gical effects				
Hazardous ingredients:					
REFRIGERANT R134A					
GASES	RAT	4H LC50	567000	ppmV	
GAGLO		411 2030	307000	ppinv	I
PENTAFLUOROETHANE					
GASES	RAT	4H LC50	800000	ppmV	
DIFLUOROMETHANE					1
GASES	RAT	LD50	520000	ppmV]
Toxicity values:	No data available.				
Symptoms / routes of exposu	ıre				
Skin contact:	There may be mild in	ritation at the site of contac	t. Frost-bite may occ	cur causing the affected	
	area to become white	e and numb.			
Eye contact:	There may be irritatio	on and redness. Corneal bu	ırns may occur. May	cause permanent	
	damage.				
Ingestion:	Not applicable.				
Inhalation:	Inhalation may produ	ce the following symptoms	: Shortness of breat	h, dizziness, weakness,	
	nausea, headache, n	arcosis, irregular cardiac a	ctivity. May cause ca	ardiac arrhythmia.	
Delayed / immediate effects:	May cause cardiac ar	rrhythmia.			
Section 12: Ecological inform	nation				
12.1. Toxicity					
Hazardous ingredients:					
-					
REFRIGERANT R134A					

Page: 6

REFRIGERANT R407C

Page: 7

GREEN ALGA (Selenastrum capricornutum)	72H ErC50	118	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	450	mg/l

DIFLUOROMETHANE

ALGAE	96H ErC50	142	mg/l
Daphnia magna	48H EC50	652	mg/l
FISH	96H LC50	1.057	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Ozone Depletion Potential (ODP): 0 (R11 = 1) R407C Global Warming Potential (GWP):

1774 (CO2 = 1) Contains fluoronated greenhouse gases covered by the Kyoto Protocol.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Product evaporates.
Recovery operations:	Consult manufacturer or supplier for information regarding recovery and recycling of the
	product. If recovery is not possible, incinerate at a licenced instalation.
Waste code number:	14 06 01
Disposal of packaging:	Return to supplier.
NB:	The user's attention is drawn to the possible existence of regional or national regulations
	regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3340

14.2. UN proper shipping name

Shipping name: REFRIGERANT GAS R 407C

(REFRIGERANT R134A; PENTAFLUOROETHANE; DIFLUOROMETHANE)

REFRIGERANT R407C

Marine pollutant: No

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: C/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Contains fluorinated greenhouse gases covered by the Kyoto Protocol.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	H220: Extremely flammable gas.
	H280: Contains gas under pressure; may explode if heated.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and
	shall be used only as a guide. This company shall not be held liable for any damage resulting
	from handling or from contact with the above product.